

BLMA

0,8 ... 2 GHz

Solid State

Standard Models

Model	Frequency Range	Output Power P_N min W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power W	Dimensions (H, D) 19"-System	Weight kg
BLMA 0820-1	0,8 ... 2 GHz	1	30 / 32 $\pm$ 2	20 / 20	75	3 HU, 350 mm	11
BLMA 0820-3	0,8 ... 2 GHz	3	34.8 / 37 $\pm$ 2	20 / 20	75	3 HU, 350 mm	11
BLMA 0820-7	0,8 ... 2 GHz	7	38.5 / 41 $\pm$ 2	20 / 20	75	3 HU, 350 mm	11
BLMA 0820-10	0,8 ... 2 GHz	10	40 / 42 $\pm$ 2	20 / 20	150	3 HU, 350 mm	11
BLMA 0820-25	0,8 ... 2 GHz	25	44 / 46 $\pm$ 2	20 / 20	200	3 HU, 350 mm	11
BLMA 0820-50	0,8 ... 2 GHz	50	47 / 49 $\pm$ 2	20 / 20	350	3 HU, 550 mm	22
BLMA 0820-100	0,8 ... 2 GHz	100	50 / 52 $\pm$ 2	20 / 20	700	3 HU, 630 mm	22
BLMA 0820-200	0,8 ... 2 GHz	200	53 / 55 $\pm$ 2	20 / 20	1200	3 HU, 630 mm	26
BLMA 0820-400	0,8 ... 2 GHz	400	56 / 58 $\pm$ 2	20 / 20	2600	6 HU, 630 mm	50
BLMA 0820-750	0,8 ... 2 GHz	750	58.8 / 61 $\pm$ 2	20 / 20	6000	15 HU, 630 mm	150

Standard Specifications:

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. for P_N -0.5 dB infinite for no damage
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)

Class of Operation: A-linear

General:

RF Input:	N-f (<8 GHz), standard on rear panel SMA-f (8 to 18 GHz), standard on front panel K-f (>18 GHz), standard on front panel
RF Output:	N-f (<8 GHz), standard on rear panel SMA-f (8 to 18 GHz), standard on front panel K-f (>18 GHz), standard on front panel
Mains Supply:	Line Power: <1000 W 100 ... 240 V AC $\pm 10\%$ / 47 ... 63 Hz Line Power: 1000 ... 3000 W 200 ... 240 V AC $\pm 10\%$ / 47 ... 63 Hz Line Power: >3000 W 3x 400 V AC $\pm 10\%$ / 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 F
Cooling:	forced air with integral blower, air intake from front air exhaust at rear

Options:

A) RF Monitor Outputs	G) Output Isolator
B) External Dual Directional Coupler	H) DC-Supply
C) IEEE-488.2 GPIB Remote Control	I) 3x 200 V AC / 60 Hz
D) Front Panel RF-Connectors	R) RS-232C Remote Control
E) Power Indication (digital)	U) USB Remote Control
F) Gain Adjustment	

Specifications are subject to change without notice

