

BLMA

26,5 ... 40 GHz

Solid State

Standard Models

Model	Frequency Range	Output Power P _N min W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power W	Dimensions (H, D) 19"-System	Weight kg
BLMA 2640-0.1	26,5 ... 40 GHz	0.1	20 / 22 ±2	20 / 20	50	3 HU, 350 mm	10
BLMA 2640-0.2	26,5 ... 40 GHz	0.2	23 / 25 ±2	20 / 20	50	3 HU, 350 mm	10
BLMA 2640-0.4	26,5 ... 40 GHz	0.4	26 / 28 ±2	20 / 20	50	3 HU, 350 mm	11
BLMA 2640-0.8	26,5 ... 40 GHz 37 ... 40 GHz	0.8 0.5	29 / 31 ±2	20 / 20	50	3 HU, 350 mm	11

Standard Specifications:

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. for P _N -0.5 dB infinite for no damage
Spurious (at P _N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A-linear

General:

RF Input:	N-f (<8 GHz), standard on rear panel SMA-f (8 to 18 GHz), standard on front panel K-f (>18 GHz), standard on front panel
-----------	--

BONN Elektronik GmbH – BLMA 26,5 ... 40 GHz

RF Output:	N-f (<8 GHz), standard on rear panel SMA-f (8 to 18 GHz), standard on front panel K-f (>18 GHz), standard on front panel
Mains Supply:	Line Power: <1000 W 100 ... 240 V AC \pm 10% / 47 ... 63 Hz Line Power: 1000 ... 3000 W 200 ... 240 V AC \pm 10% / 47 ... 63 Hz Line Power: >3000 W 3x 400 V AC \pm 10% / 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 F
Cooling:	forced air with integral blower, air intake from front air exhaust at rear

Options:

- | | |
|--------------------------------------|---------------------------|
| A) RF Monitor Outputs | G) Output Isolator |
| B) External Dual Directional Coupler | H) DC-Supply |
| C) IEEE-488.2 GPIB Remote Control | I) 3x 200 V AC / 60 Hz |
| D) Front Panel RF-Connectors | R) RS-232C Remote Control |
| E) Power Indication (digital) | U) USB Remote Control |
| F) Gain Adjustment | |

Specifications are subject to change without notice

BONN Elektronik GmbH – BLMA 26,5 ... 40 GHz



Rudolf-Diesel-Str.18 · D-85521 Ottobrunn · Tel +49 (0)89/608 754-0 · Fax +49 (0)89/608 754-99
email: info@bonn-elektronik.com · home: www.bonn-elektronik.com