

BLMA

4 ... 18 GHz

Solid State

Standard Models

Model	Frequency Range	Output Power P_N min W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power W	Dimensions (H, D) 19"-System	Weight kg
BLMA 4018-5	4 ... 18 GHz	5	37 / 39 $\pm$ 2	20 / 20	200	3 HU, 350 mm	13

Standard Specifications:

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. for P_N -0.5 dB infinite for no damage
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A-linear

General:

RF Input:	N-f (<8 GHz), standard on rear panel SMA-f (8 to 18 GHz), standard on front panel K-f (>18 GHz), standard on front panel
RF Output:	N-f (<8 GHz), standard on rear panel SMA-f (8 to 18 GHz), standard on front panel K-f (>18 GHz), standard on front panel
Mains Supply:	Line Power: <1000 W 100 ... 240 V AC $\pm$ 10% / 47 ... 63 Hz

BONN Elektronik GmbH – BLMA 4 ... 18 GHz

Elapsed Time Meter:	Line Power: 1000 ... 3000 W 200 ... 240 V AC $\pm 10\%$ / 47 ... 63 Hz
Ambient Temperature:	Line Power: >3000 W 3x 400 V AC $\pm 10\%$ / 47 ... 63 Hz
Storage Temperature:	via status display
Relative Humidity:	0 ... +45 °C
Operating Altitude:	–20 ... +85 °C
Vibration and Shock:	up to 95% (non-condensing)
Cooling:	up to 2000 m above sea level
	MIL-STD-810 F
	forced air with integral blower, air intake from front air exhaust at rear

Options:

- | | |
|--------------------------------------|---------------------------|
| A) RF Monitor Outputs | G) Output Isolator |
| B) External Dual Directional Coupler | H) DC-Supply |
| C) IEEE-488.2 GPIB Remote Control | I) 3x 200 V AC / 60 Hz |
| D) Front Panel RF-Connectors | R) RS-232C Remote Control |
| E) Power Indication (digital) | U) USB Remote Control |
| F) Gain Adjustment | |

Specifications are subject to change without notice