

BLWA

1 ... 500 MHz

Solid State

Standard Models

Model	Frequency Range	Output Power P_N min W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power W	Dimensions (H, D) 19"-System	Weight kg
BLWA 0150-2	1 ... 500 MHz	2	33 / 35 $\pm$ 2	20 / 20	75	3 HU, 350 mm	11
BLWA 0150-5	1 ... 500 MHz	5	37 / 39 $\pm$ 2	20 / 20	100	3 HU, 350 mm	11
BLWA 0150-10	1 ... 500 MHz	10	40 / 42 $\pm$ 2	20 / 20	150	3 HU, 350 mm	12
BLWA 0150-25	1 ... 500 MHz	25	44 / 46 $\pm$ 2	20 / 20	180	3 HU, 350 mm	13
BLWA 0150-50	1 ... 500 MHz	50	47 / 49 $\pm$ 2	20 / 20	600	4 HU, 550 mm	25
BLWA 0150-100	1 ... 500 MHz	100	50 / 52 $\pm$ 2	20 / 20	1300	4 HU, 630 mm	30

Standard Specifications:

Input Power:	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. for P_N -0.5 dB; infinite for no damage
Spurious (at P_N):	-50 dBc typ. (excluding harmonics)
Class of Operation:	A linear or A-B linear

General:

RF Input:	N-f; standard on rear panel
-----------	-----------------------------

RF Output:	standard on rear panel N-f (P_N up to 1 kW) 7/16-f ($P_N > 1$ kW) 13/30-f or 1 5/8" EIA ($P_N > 2$ kW)
Mains Supply:	Line Power: <1000 W 100 ... 240 V AC $\pm 10\%$ / 47 ... 63 Hz Line Power: 1000 ... 3000 W 200 ... 240 V AC $\pm 10\%$ / 47 ... 63 Hz Line Power: >3000 W 3x 400 V AC $\pm 10\%$ / 47 ... 63 Hz
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +45 °C
Storage Temperature:	-20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	MIL-STD-810 F
Cooling:	forced air with integral blower, air intake from front air exhaust at rear

Options:

A) RF Monitor Outputs	F) Gain Adjustment
B) External Dual Directional Coupler	H) DC-Supply
C) IEEE-488.2 GPIB Remote Control	I) 3x 200 V AC / 60 Hz
D) Front Panel RF-Connectors	R) RS-232C Remote Control
E) Power Indication (digital)	U) USB Remote Control

Specifications are subject to change without notice



Rudolf-Diesel-Str.18 · D-85521 Ottobrunn · Tel +49 (0)89/608 754-0 · Fax +49 (0)89/608 754-99
email: info@bonn-elektronik.com · home: www.bonn-elektronik.com