

TWAL

18 ... 26,5 GHz

Travelling Wave Tube

Standard Models

Model	Frequency Range	Output Power P_N min W	Gain min / typ dB	Harmonics 2nd / 3rd dBc	Line Power W	Dimensions (H,D) 19"-System	Weight kg
TWAL 1826-40	18 ... 26,5 GHz	40	46 / 52 $\pm$ 6	15 / 20	1200	3+5 HU, 610 mm	41
TWAL 1826-120	18 ... 26,5 GHz	120	50.8 / 57 $\pm$ 6	15 / 20	750	6 HU, 630 mm	45

Standard Specifications:

Input Power	0 dBm (1 mW) max.
Overdrive Protection:	up to +10 dBm for no damage
Input Impedance:	50 Ohm nominal
Output Impedance:	50 Ohm nominal
Input VSWR:	<2:1 typ.
Load VSWR:	2:1 max. for P_N -0.5 dB infinite for no damage
Spurious (at P_N):	-50 dBc typ.(excluding harmonics)
Noise Figure:	20 dB max.
Class of Operation:	A-linear

General:

RF Input:	1 ... 18 GHz: N-f; standard on rear panel 18 ... 40 GHz: k-f; standard on rear panel
RF Output (1 kW):	standard on rear panel 1 ... 10 GHz: N-f 8 ... 18 GHz: WRD 750 18 ... 26.5 GHz: WR 42

RF Output (>1 kW):	26.5 ... 40 GHz: WR 28 standard on rear panel 1 ... 8 GHz: 7/16 8 ... 18 GHz: WRD 750
Gain Adjustment:	via status display (<4 GHz) or via thumbwheel (>4 GHz)
RF Monitor Output	–50 dB forward
Mains Supply:	200 ... 264 V AC / 47 ... 63 Hz
Power Meter:	via status display
Elapsed Time Meter:	via status display
Ambient Temperature:	0 ... +40 °C
Storage Temperature:	–20 ... +85 °C
Relative Humidity:	up to 95% (non-condensing)
Operating Altitude:	up to 2000 m above sea level
Vibration and Shock:	normal laboratory environment
Cooling:	forced air with integral blower, air intake and exhaust at rear

Options:

A) Reverse Monitor	G) Output Isolator
B) External Dual Directional Coupler	M) 115 V AC / 47 ... 63 Hz
C) IEEE–488.2 GPIB Remote Control	N) Harmonic Filter
	R) RS–232C Remote Control
	U) USB Remote Control
(1)	Combiner is limiting the actual frequency range

Specifications are subject to change without notice



Rudolf-Diesel-Str.18 · D-85521 Ottobrunn · Tel +49 (0)89/608 754-0 · Fax +49 (0)89/608 754-99
email: info@bonn-elektronik.com · home: www.bonn-elektronik.com